



PRODUCT SPECIFICATION DATA SHEET



BOSS ZRX 4-STROKE MOTORCYCLE OILS

Customer Benefits:

BOSS ZRX 4-STROKE MOTORCYCLE OILS are formulated to meet the special engineering requirements of the motorcycle wet clutch systems. These products have a carefully balanced premium additive system that will give outstanding deposit control minimize sludge and varnish, and control wear under the most severe service condition. These multi-viscosity formulas offer superior high temperature protection along with easier starting and a rapid oil flow

PERFORMANCE SPECIFICATIONS:

SAE VISCOSITY GRADE	10W40	20W50
Density @ 15.6 C, Kg/L	0.8866	0.8927
Viscosity, CST @ 40 C	95.7	171
Viscosity, CST @ 100 C	13.4	19.0
Viscosity Index	140	126
CCS Viscosity, cP@-10°C	3300	4200
Flash Point, C	204	226.7
Pour point, C	-31.7	- 26.1
Sulphated Ash, Mass %	1.10	1.15
Filter Ability Test (GM EOFS)	Pass	Pass
Foam Test (D-892)	Pass	Pass

Applications:

- Exceeds API Service Categories SL/SJ/CD/CF
- Meets and exceeds performance requirements of BMW, HARLEY DAVIDSON, HONDA and KAWASAKI