



PRODUCT SPECIFICATION DATA SHEET



BOSS MULTI-GRADE PUMP JACK 150

Customer Benefits:

BOSS Lubricants Multi-Grade Pump Jack 150 is formulated to offer all season capability. Its low temperature properties allow excellent low temperature start-up. This product is design to operate in a temperature range from -30°C to +75°C. BOSS Lubricants Multi-Grade Pump Jack 150 is very appealing to customers utilizing this product on indoor and outdoor applications. This product can be used in such applications as out door conveyor systems, pump jack gear boxes, and overhead cranes.

Properties:

Grade	150
<u>Kinematic Viscosity (cSt)</u>	
Viscosity @ 100°C	19.14
Viscosity @ 40°C	150.0
Viscosity Index	142
Density @ 15°C	0.8602 Kg/L
Pour Point (°C)	-30°C
Flash Point (°C)	217°C

Performance Benefits:

Excellent Load Carrying Capability – The EP additives in this gear oil are activated by high temperatures caused by shock loading, and act as a boundary lubricant between points on the gears.

All Season Gear Protection – BOSS Multi-Grade Pump Jack 150 is specially designed to handle a wide range of differing temperatures thus reducing service intervals and costs associated with this.

Improved Rust and Corrosion – Our product utilizes anti-foam additives to reduce oil “frothing” caused by the gears during operation, which maximizes the total gear protection.

Increased Water Separation Capability – Quick water separation prevents degradation of the gears.