



# PRODUCT SPECIFICATION DATA SHEET



---

## BOSS PENETRATING OIL & LUBRICANT

---

### Customer Benefits:

This multi-purpose deep penetrating lubricant, which drives out moisture, leaves a long lasting highly protective film that contains special additives which dramatically reduces wear due to friction. This product far outperforms conventional lubricating oils and other multi-purpose products.

### PERFORMANCE SPECIFICATIONS:

Physical State	Aerosol
Appearance	Liquid
Odor	Solvent Odor
Vapor Pressure	Aerosol-40psi
Vapor Density (air=1)	4.9
Boiling Point, C	160
Specific Gravity, kg/l	0.88
Flash Point, C	>40C TOC

### Properties:

- Penetrates quickly
- Lubricates
- Reduces friction and wear
- Displaces moisture
- Protects against rust

### NOTE: Handling risks & Precautions:

RISKS: Contents under pressure. Container may explode if heated above 50C. Combustible liquid. Direct inhalation of contents may be harmful. May cause irritation to eyes, skin and respiratory tract. May be harmful if swallowed.

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30<sup>th</sup> Street S.E. Calgary, AB T2C 1R4  
Website: [www.bosslubricants.com](http://www.bosslubricants.com)

PRECAUTION: Do not puncture, incinerate or store above 50C. Do not place on hot water or store near radiators, stoves or other sources of heat. Do not store or spray in or around flame or spark. Use in well ventilated area. Avoid contact with skin and eyes. Wear eye protection. Use with adequate ventilation. Do not breathe vapors.