



**BOSS**  
**LUBRICANTS**



~ Est. 1992 ~

## BOSS High Mileage Synthetic Blend Engine Oil

BOSS Lubricants Synthetic Blend High Mileage oils are blended with special quality additive packages and base oils to perform in engines that have high mileage over 100,000 km. Temperature increases can rise with higher mileage engines, therefore, is advantageous to match the increase temperature with a product that can handle it. High Mileage engines can have steady build-up of deposits or burn off from catalytic converters, therefore an additive package with synthetic base oil in it helps to combat those contaminants.

BOSS Lubricants Syn Blend High Mileage oils are available in 0w20, 5w20, and 5w30 grades, and meet or exceed the API service GF-6A oil specifications.

### TYPICAL PROPERTIES

ISO GRADE	0W20	5W20	5W30
Density @ 15°C	0.852	0.855	0.861
Kinematic VISCOSITY CST @ 40°C (D445)	46.14	50.8	62.7
Kinematic VISCOSITY @ 100°C (D445)	8.6	8.85	10.8
Viscosity INDEX (D2270)	160	153	162
CCS Viscosity (D2602)	342	342	343
CCS Viscosity (D2602) CP @ -35°C	5760	N/A	N/A
CCS Viscosity (D2602) CP @ -30°C	N/A	6050	6470
Flash Point (D92) °C	224	219	225

### SUITABLE FOR USE IN VEHICLES REQUIRING THE FOLLOWING OEM SPECIFICATIONS:

- API GF-6
- Chrysler MS 6395
- Ford WSS-M2C947-A/ WSS-M2C947-B1
- GM dexos1™ Gen 2