

MULTI GRADE PUMP JACK OIL

Designed for pump jack operations in variable temperature conditions. Extreme pressure additives ensure effective anti wear protection. These oils also contain rest and oxidation inhibitors and anti foam agents for optimal performance.

ISO GRADE	100	150
AGMA GRADE	3EP	4EP
DENSITY @ 15°C	0.8996	0.8602
KINEMATIC VISCOSITY CST @ 40°C	100	150
KINEMATIC VISCOSITY CST @ 100°C	11.4	14.8
VISCOSITY INDEX	95	95
FLASH POINT, °C	233	243
POUR POINT, °C	-31	-27
TIMKEN OK LOAD, KG	27	27

APPLICATIONS MEETS AND EXCEEDS SPECIFICATIONS

- AGMA 250.40
- US STEEL 224

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





MULTI GRADE PUMP JACK OIL

APPLICATIONS MEETS AND EXCEEDS SPECIFICATIONS

- GARDNER-DENVER
- DRESSER RAND

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

