

VEHICULAR NATURAL GAS ENGINE OILS

VNGEO is a premium quality, low ash, dispersant-detergent engine oil specifically designed for use in vehicular natural gas engines engine oils. This product is formulated with premium Group II base stocks and an excellent premium additive system. Provide maximum protection against high temperature oxidation wear, rust, corrosion and viscosity breakdown while keeping your engine exceptionally clean and free of sludge and varnish. High TBN reserve effectively neutralizes combustion formed corrosive acids which help protect turbo bearings and other vital engine surfaces.

SAE GRADE	10W30	15W40
SPECIFIC GRAVITY, KG/L	0.8655	0.869
KINEMATIC VISCOSITY (D445) CST @ 40°C	68.65	116
KINEMATIC VISCOSITY (D445) CST @ 100°C	10.64	14.7
VISCOSITY INDEX (D2270)	110	140
FLASH POINT (D92), °C	207	228
POUR POINT (D97), °C	-36	-32
API SERVICE CATEGORY	CF	CF
TBN	5.42	6.07
ASH	0.26	0.27

^{*} **NOTE**: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4







PRODUCT SPECIFICATION data sheet

VEHICULAR NATURAL GAS ENGINE OILS

BOSS VNGEO 15w40 meets the following requirements for CNG, LNG or LPG powered engines:

- Detroit Diesel 7SE272 9510
- Cummins CES 20085
- Volvo CNG
- Mack CNG
- Renault RGD
- Hyundai CNG

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



