

CD-50W SYNTHETIC TRANSMISSION FLUID

Designed with a very low pour point and a high viscosity for outstanding low temperature flow and high temperature lubrication. A superb transmission fluid for year round use for on and off highway equipment.

SAE GRADE	50
DENSITY @ 15.5°C, KG/L	0.8697
KINEMATIC VISCOSITY (D445) CST @ 40°C	150
KINEMATIC VISCOSITY (D445) CST @ 100°C	18.5
VISCOSITY INDEX (D2270)	130
FLASH POINT (D92), °C	268
POUR POINT (D97), °C	-36

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: CD
- API: GL-1, GL-2, GL-3

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





CD-50W SYNTHETIC TRANSMISSION FLUID

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- EATON & ROCKWELL

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

