

## MULTI VEHICLE SYNTHETIC BLEND ATF

This advanced additive formulation system which uses specific selected synthetic and mineral base oils while possessing a shear-stable polymer to provide exceptional friction and anti-shudder durability, improving low temperature operability and resistance to oxidation, rust and thermal degradation. This blend meets the stringent wear, friction and operational requirements of most automatic transmissions for a smooth driving experience.

TYPICAL PROPERTIES	MV ATF
SPECIFIC GRAVITY @ 15°C	0.8598
KINEMATIC VISCOSITY CST @ 40°C	35.43
KINEMATIC VISCOSITY CST @ 100°C	7.56
VISCOSITY INDEX (D2270)	189
BROOKFIELD VISCOSITY @ -40°C	11000
FLASH POINT (D92), °C	N/A
POUR POINT (D97), °C	-51
COLOUR	RED

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- MAN 339 TYPE Z1, Z2, V1
- MERCON V (XT-5-QM, XT-5-DM)

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



## MULTI VEHICLE SYNTHETIC BLEND ATF

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- ZF TE-ML 14B

#### SUITABLE FOR USE IN:

- AUDI G 052 025, 052 162, 055 025
- BMW P/N 83 22 0 024 359, ETL-8072B
- BMW P/N 83 22 0 403 249, ETL-8072B
- BMW P/N 83 22 9 407 807, LT 711 41
- DEXRON III G/H, DEXRON II, DEXRON, AW1
- VOLVO P/N 1161540-8
- CHRYSLER AS68RC, DIAMOND SP-III
- CHRYSLER P/N 68043742AA (DEX VI)
- JWS 3309, ANY 3309
- MAZDA ATF M-III, MV, T-IV
- SUZUKI 3314, 3317
- FORD P/N XT-2-SM (SYN MERC)
- NISSAN MATIC-D, J, K, 402
- SHELL 3403, LA2634, TEXACO 7045-E, ETL-8072B
- ESSO 71141
- BMW P/N 83 22 0 0246 922, ETL-7045E
- BMW P/N 83 22 9 407 765, LA 2634
- BMW 7045E, LA2634, LT71141
- HONDA DW-1, Z-1
- HYUNDAI/KIA/MITSUBISHI DIAMOND SP-II & SP-III, RED-1, SP-IV
- CHRYSLER P/N 05127382AA
- IDEMITSU K17
- M315-2004 JASO 1A, 2A
- MB236.1,2,5,6,7,9,10,11
- FORD P/N XT-2-DX (MERC)
- MERCON, FORD ESP-M2C166-H
- TEXACO N402
- HYUNDAI NSWS9638

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



## MULTI VEHICLE SYNTHETIC BLEND ATF

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- FUCHS 3353
- MINI P/N 83 22 0 402 413
- SAAB P/N 22 717 466, 93 165 147 (AW-1)
- PORSCHE P/N 999 917 547 00 (A2)
- SHELL 3403 M115
- TOYOTA T-II, T-III, T-IV, WS, FORD, XT8QAW
- JWS 3324
- VOLVO PASSENGER CAR (4-6 SP)
- VW G 052 025, 162, 099, 055 025
- IDEMITSU APOROIL ATF HP
- SATURN P/N21005966
- JAGUAR P/N WSS-M2C922-A-1
- VW P/N GUS000 162
- SUBARU ATF, ATF-HP
- SATURN T-IV, GM-TASA, T-IV ATF, GM WS ATF
- VOITH 55.6335 (G607)
- VOLVO 97340, 97341
- ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

