

POWER TRANSMISSION FLUID TO-4

Designed for heavy duty power-shift transmissions. This unmatched formulation provides improved power transfer performance, wear resistance, high horse power output and increased loads at higher temperatures.

SAE GRADE	10W	30W	50W
DENSITY @ 15.5°C, KG/L	0.8899	0.8944	0.8996
KINEMATIC VISCOSITY (D445) CST @ 40°C	44	92.5	220.4
KINEMATIC VISCOSITY (D445) CST @ 100°C	6	10.5	17.9
VISCOSITY INDEX (D2270)	101	95	94
FLASH POINT (D92), °C	197	209	220
POUR POINT (D97), °C	-37	-23	-15

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- ALLISON: C-4, C-3 (SAE 10W & 30W GRADES)
- CATERPILLAR: TO-4 (ALL SAE GRADES)

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





POWER TRANSMISSION FLUID TO-4

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- KOMATSU MICRO CLUTCH (ALL SAE GRADES)

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

