

## SYNTHETIC BLEND TO-4M FLUID

Formulated from premium base stocks and a specific additive system that meets the challenging demands of modern equipment. This multi viscosity product has outstanding performance over a wide temperature range and provides both excellent high temperature film thickness and low temperature pump ability for wear protection under severe loading conditions. This blend also provides excellent friction material and elastomer compatibility, while guarding against gear wear, rust, corrosion, foaming and oxidation.

SAE GRADE	TO-4M
DENSITY @ 15.5°C, KG/L	0.872
KINEMATIC VISCOSITY (D445) CST @ 40°C	104.8
KINEMATIC VISCOSITY (D445) CST @ 100°C	14.44
VISCOSITY INDEX (D2270)	126
FLASH POINT (D92), °C	186
POUR POINT (D97), °C	-36

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- ALLISON: C-4
- CATERPILLAR: TO-4 & TO-4M

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*





## SYNTHETIC BLEND TO-4M FLUID

### APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- KOMATSU MICRO CLUTCH

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

