

## SYNTHETIC GL-4 GEAR OIL

Specifically designed to meet the service requirements of API: GL-4. This synthetic gear oil is formulated for superior flow ability, to minimize gear wear, reduce frictional drag and protect against heavy loading failures in extreme weather conditions.

<b>SAE GRADE</b>	<b>75W90</b>
DENSITY @ 15.5°C, KG/L	0.8762
KINEMATIC VISCOSITY (D445) CST @ 40°C	92.32
KINEMATIC VISCOSITY (D445) CST @ 100°C	15.42
VISCOSITY INDEX (D2270)	141
FLASH POINT (D92), °C	204
POUR POINT (D97), °C	-48
BROOKFIELD VISCOSITY @ -40°C	133000

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: GL-4
- SAE: 75W90

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

