

## ZRX 4-STROKE MOTORCYCLE OILS

These multi viscosity premium motorcycle oils are formulated to provide easier start up, rapid oil flow, superior high temperature protection while meeting special requirements of the motorcycles wet clutch system. An exceptional and carefully balanced additive system that minimizes sludge, varnish deposits and wear on your bikes engine.

SAE GRADE	10W40	20W50
DENSITY @ 15.6°C, KG/L	0.8866	0.8927
KINEMATIC VISCOSITY (D445) CST @ 40°C	95.7	171
KINEMATIC VISCOSITY (D445) CST @ 100°C	13.4	19
VISCOSITY INDEX (D2270)	140	126
FLASH POINT (D92), °C	204	226.7
POUR POINT (D97), °C	-31.7	-26.1
CCS VISCOSITY, CP @ -10°C	3300	4200
SULPHATED ASH, MASS%	1.1	1.15
FILTER ABILITY	PASS	PASS
FOAM TEST	PASS	PASS

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*





## ZRX 4-STROKE MOTORCYCLE OILS

- EXCEEDS API SERVICE CLASSIFICATION SL, SJ, CD, CF

- MEETS AND EXCEEDS THE PERFORMANCE REQUIREMENTS FOR BMW, HARLEY DAVIDSON, HONDA, KAWASAKI

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



**ILMA**  
Independent Lubricant Manufacturers Association