

CONCRETE FORM OIL

BOSS Concrete Form Oil is formulated to impart a separation film to all types of concrete forms. This non-staining material consists of a light mineral oil which is combined with a chemical agent to allow better than average cling tendencies to forms. The combination physically repels both water and concrete and is designed to be non-toxic and does not require a WHMIS label

| | |
|---------------------------------|--------|
| SPECIFIC GRAVITY @ 15.5°C | 0.8406 |
| KINEMATIC VISCOSITY CST @ 40°C | 4.97 |
| KINEMATIC VISCOSITY CST @ 100°C | 1.75 |
| FLASH POINT, °C | 45 |
| POUR POINT, °C | -30 |

APPLICATIONS

- FOR APPLICATIONS TO FORMS PRIOR TO CONCRETE PLACEMENT TO FACILITATE FORM REMOVAL CONCRETE SET.
- THE APPLICATOR SHOULD AVOID PUDDLES, RUNS AND EXCESSIVE SPRAY DRIFT.
- IT IS READY TO USE BUT CAN BE DILUTED WITH MINERAL SPIRITS OR ALIPHATIC SOLVENTS FOR SPRAY APPLICATION CONTROL.
- CAN BE STORED AND APPLIED AT BELOW FREEZING TEMPRATURES WHEN NEEDED.

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





CONCRETE FORM OIL

APPLICATIONS

- CAN BE USED ON FORMS THAT HAVE BEEN PREVIOUSLY TREATED WITH FORM OIL.

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

