

## HEAVY DUTY EXTREME DIESEL ENGINE OILS API CK-4

Specifically engineered to meet the latest requirements for EGR/EGP engines and the new federal regulations mandating reduced fuel consumption and lower emissions. For today's demanding engine requirements CK-4 oils must pass 2 new tests to evaluate oxidation stability and aeration control. API CK-4 15W40 meets or exceeds most OEM manufacturer's specifications and is backward compatible with CJ-4, CI-4 PLUS, CI-4 and CH-4. 10W30 meets and exceeds API CK-4 and is designed to maximize fuel economy in today's current engines and utilizes group II+ type baseoils.

SAE GRADE	10W30	15W40
SPECIFIC GRAVITY @ 15.6°C, CST	0.0865	0.0869
KINEMATIC VISCOSITY (D445) CST @ 40°C	81.7	113.9
KINEMATIC VISCOSITY (D445) CST @ 100°C	12.2	15.6
VISCOSITY INDEX (D2270)	145	145
FLASH POINT (D92), °C	237	226
POUR POINT (D97), °C	-39	-33
VISCOSITY, CCS CP @ -20°C	6200	5500
ASH SULPHATE, WT%	1.00	1.00

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



## HEAVY DUTY EXTREME DIESEL ENGINE OILS API CK-4

**SAE GRADE**

**10W30**

**15W40**

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS

**MEETS OR EXCEEDS THE FOLLOWING API SERVICE AND OEM SPECIFICATIONS REQUIREMENTS:**

- API: CK-4, CJ-4, CI-4PLUS, CI-4, CH-4
- CATERPILLAR: ECF-2, ECF-3
- CUMMINS: CES 20081, CES 20086, CES 20087
- DAIMLER: MB 228.31
- DETROIT DIESEL: DFS 93K222, DFS 93K218, DFS 93K233
- MTU: CATEGORY 2.1
- RENAULT: RLD-4, RLD-3
- VOLVO: VDS 4.5, 4, 3

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

