

HIGH PERFORMANCE (HP) AUTOMOTIVE ENGINE OILS 5000 SERIES

This engine oil is formulated for turbo charged, naturally aspirated gasoline, natural gas and propane engines in passenger vehicles and light duty service trucks. It lubricates, cools and protects high revving turbo charged engines that operate at high temperatures. This formulation helps protect engines by controlling varnish deposits, rust, and corrosion wear. It also helps protect against the increasing impact of low-speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines (GDI).

SAE GRADE	5W20	5W30	10W30
DENSITY (D4052) KG/M @ 15°C	863	863	872
KINEMATIC VISCOSITY (D445) CST @ 40°C	49.7	58.9	69.5
KINEMATIC VISCOSITY (D445) CST @ 100°C	8.6	10.6	10.6
VISCOSITY INDEX (D2270)	150	155	140
CCS VISCOSITY (D2602):	341	341	N/A
CCS VISCOSITY (D2602) CP @ -30°C	6100	6300	N/A
CCS VISCOSITY (D2602) CP @ -25°C	N/A	N/A	6300
FLASH POINT (D92), °C	218	224	234
POUR POINT (D97), °C	-42	-42	-36
COLOUR (ASTM)	3	3	3
ASH SULPHATE, MASS%	0.92	0.92	0.92

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



HIGH PERFORMANCE (HP) AUTOMOTIVE ENGINE OILS 5000 SERIES

SAE GRADE

5W20

5W30

10W30

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

- GASOLINE ENGINES FOR PASSENGER VEHICLES AND TRUCKS THAT SPECIFY API SERVICE SN PLUS, SM, SL, SJ, SH, SG, SF REQUIREMENTS.
- PROPANE ENGINES FOR PASSENGER VEHICLES AND TRUCKS
- NATURAL GAS ENGINES
- UPHOLDS THE WARRANTY REQUIREMENTS FOR PASSENGER VEHICLES AND LIGHT DUTY TRUCKS THAT SPECIFY ILSAC STARBURST GF-1, GF-2, GF-3, GF-4 AND GF-5 ENGINES
- MEETS AND EXCEEDS THE REQUIREMENTS FOR GM6094M, CHRYSLER MS6395, FORD WSS-M2C930-A & WSS-M2C945-A

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

